



HALEY & ALDRICH, INC.
6500 Rockside Road
Suite 200
Cleveland, OH 44131
216.739.0555

MEMORANDUM

16 October 2016
File No. 40616-108

SUBJECT: Inflow Design Flood Control System Plan
Pond 004
Associated Electric Cooperative, Inc.
New Madrid Power Plant
New Madrid, Missouri

Haley & Aldrich, Inc. (Haley & Aldrich) has developed this Inflow Design Flood (IDF) Control System Plan (Plan) on behalf of Associated Electric Cooperative, Inc. (AECI) for the existing coal combustion residuals (CCR) surface impoundment referred to as Pond 004 at the New Madrid Power Plant in New Madrid, Missouri. This has been completed based on requirements of the Environmental Protection Agency (EPA) 40 CFR Parts 257 and 261, "Hazardous and Solid Waste Management System; Disposal of Coal Combustion Residuals from Electric Utilities" (CCR Rule), specifically section §257.82. The Pond 004 existing conditions and supporting documentation has been reviewed and associated stormwater modeling and analysis performed to satisfy the Inflow Design Flood Control System Plan requirements of CCR Rule section §257.82 as described below.

§257.82(a): The owner or operator of an existing or new CCR surface impoundment or any lateral expansion of a CCR surface impoundment must design, construct, operate, and maintain an inflow design flood control system as specified in paragraphs (a)(1) and (a)(2) of this section.

§257.82(a)(1): The inflow design flood control system must adequately manage flow into the CCR unit during and following the peak discharge of the inflow design flood specified in paragraph (a)(3) of this section.

Pond 004 is a coal combustion residuals (CCR) surface impoundment used for settling and temporary wet storage of bottom ash and boiler slag sluiced from the NMPP. This impoundment also manages plant process water and coal pile runoff. CCR reclamation and processing equipment and associated activities also occur at the impoundment. This impoundment is used sparingly as a redundant unit for Pond 003 (meaning it does not receive constant flows and more likely flows on the order of 2 to 3 times a year), primarily during plant outages and when sluice pipes need repair.

Process water and CCR are discharged into the impoundment via pipelines located at the northwestern portion of the impoundment. The discharged water and CCR flow through an open channel to a clear portion of the unit in the southern end. Decant water discharges from the impoundment flow to a concrete drop inlet structure with concrete stoplogs used to

manage water elevation. A discharge pipe directs water through the dike and into the Mississippi River.

Typically, there are periods (i.e. months) where this impoundment receives nominal or no flow from the plant during typical operating conditions. During times when the plant does discharge into this unit, process water flows from the plant to this impoundment include typical average monthly flows along with specific flow types that have peak instantaneous or daily flows based on plant operations as stated in the plant NDPES permit. However, those peak flows are limited, able to be managed, and occur more as instantaneous peaks in a day rather than sustained peak flows. We have modeled two scenarios accordingly.

For modeling purposes, the first model assumes higher operating levels for the impoundment and analysis of the design storm and average monthly flows. The second model assumes operation of the unit at a lower water level under the assumption that staff remove stoplogs when normal conditions exist and also when large storm events or higher plant flows are anticipated. Based on operational considerations, this second model assumes that the peak instantaneous flows are maintained for a 12-hour period (typically those flows are intermittent when occurring and plant ability to manage when those flows occur - so this is a conservative assumption) and then average flows thereafter.

Hydrologic and hydraulic modeling for this Pond 004 IDF Control System Plan was performed using HydroCAD Stormwater Modeling System, version 10.00-12 (HydroCAD) in conjunction with the appropriate IDF as determined per the Hazard Potential Classification Assessment performed under separate cover.

When Pond 004 is maintained temporarily at a higher water surface elevation (WSEL) (El. 295.6), the results of the HydroCAD analysis confirm the IDF control system for Pond 004 adequately manage flow into the impoundment during and following the IDF peak storm discharge by containing the flood within the impoundment along with the average process water inflows and discharges. We also evaluated the second scenario of AECL removing stoplogs to lower the initial water surface when a significant rainfall event and/or process water discharge is anticipated (this is the more typical normal operating conditions). This second scenario includes removing two (2) stoplogs (24-in. total) from the decant structure to decrease the peak water surface elevation in the unit to El. 293.6 (more typical operating condition) and to include continuous instantaneous peak process water inflows for a 12-hour period (which is conservative due to ability to manage peak flows and due to limited use of this impoundment). Similarly, Pond 004 adequately manages flow into the impoundment. **Table I** summarizes the results of the IDF peak discharge during temporary operation and a lowered normal stoplog scenario. The output from the two HydroCAD model simulations is provided as **Appendix A**. See **Figure 1** for the Pond 004 existing site plan.

Table I: HydroCAD Output Summary – 1,000 Flood		
	High Operating Conditions	Lower Operating Conditions (Normal)
Peak flood level (ft)	297.2	298.7
Minimum Dike Elevation	301.0	301.0
Minimum freeboard (ft)	3.8	2.3
Peak inflow (cfs)	84.6	104.1

§257.82(a)(2): *The inflow design flood control system must adequately manage flow from the CCR unit to collect and control the peak discharge resulting from the inflow design flood specified in paragraph (a)(3) of this section.*

The outlet control structure was noted in “Final Report Round 7 Dam Assessment” completed by GZA GeoEnvironmental, Inc. dated 3 June 2011. Pertinent pages providing the required information have been provided as **Appendix B**. Supplemental hand measurements of the structure were also made by AECl. Based on the HydroCAD analysis, the IDF control system for Pond 004 was determined to adequately manage flow from the impoundment by collecting and controlling the IDF peak discharge. The peak level and resulting freeboard in Pond 004 during the 1,000-year flood is noted in Table I (above). The HydroCAD model simulation output is provided as **Appendix A**.

§257.82(a)(3): *The inflow design flood is:*

- i. *For a high hazard potential CCR surface impoundment, as determined under § 257.73(a)(2) or § 257.74(a)(2), the probable maximum flood;*
- ii. *For a significant hazard potential CCR surface impoundment, as determined under § 257.73(a)(2) or § 257.74(a)(2), the 1,000-year flood;*
- iii. *For a low hazard potential CCR surface impoundment, as determined under § 257.73(a)(2) or § 257.74(a)(2), the 100-year flood; or*
- iv. *For an incised CCR surface impoundment, the 25-year flood.*

Pond 004 was determined to be significant hazard potential; therefore, the design event is the 1,000-year, 24-hour storm. The basis of the determination is discussed in Initial Hazard Potential Classification Assessment, Pond 004 dated October 2016. The 1,000-year storm characteristics were detailed in the NOAA Atlas 14 Point Precipitation Frequency Estimates dated 15 September 2016 and prepared by the National Weather Service. Pertinent pages providing the required information have been provided as **Appendix C**.

§257.82(b): Discharge from the CCR unit must be handled in accordance with the surface water requirements under § 257.3–3.

§257.3-3(a): For purposes of section 4004(a) of the Act, a facility shall not cause a discharge of pollutants into waters of the United States that is in violation of the requirements of the National Pollutant Discharge Elimination System (NPDES) under section 402 of the Clean Water Act, as amended.

§257.3-3(b): For purposes of section 4004(a) of the Act, a facility shall not cause a discharge of dredged material or fill material to waters of the United States that is in violation of the requirements under section 404 of the Clean Water Act, as amended.

§257.3-3(c): A facility or practice shall not cause non-point source pollution of waters of the United States that violates applicable legal requirements implementing an areawide or Statewide water quality management plan that has been approved by the Administrator under section 208 of the Clean Water Act, as amended.

Discharge from the Pond 004 is subject to the Missouri State Operating Permit issued by the Missouri Department of Natural Resources.

§257.82(c)(1): Content of the plan. The owner or operator must prepare initial and periodic inflow design flood control system plans for the CCR unit according to the timeframes specified in paragraphs (c)(3) and (4) of this section. These plans must document how the inflow design flood control system has been designed and constructed to meet the requirements of this section. Each plan must be supported by appropriate engineering calculations. The owner or operator of the CCR unit has completed the inflow design flood control system plan when the plan has been placed in the facility's operating record as required by § 257.105(g)(4).

This document and all attachments serve as the initial IDF Plan. Periodic inflow design flood control system plans will be prepared and placed in the facility operating record at 5-year increments or whenever there is a change in conditions that would affect the Plan.

§257.82(c)(2): Amendment of the plan. The owner or operator of the CCR unit may amend the written inflow design flood control system plan at any time provided the revised plan is placed in the facility's operating record as required by § 257.105(g)(4). The owner or operator must amend the written inflow design flood control system plan whenever there is a change in conditions that would substantially affect the written plan in effect.

The IDF Plan will be amended at least 60 days prior to a planned change in the operation of the facility or the CCR impoundment, or no later than 60 days after an unanticipated event requires

the need to revise the IDF Plan. If the Plan needs to be revised after closure activities have commenced, the Plan will be revised no later than 30 days following the triggering event.

Any amendments to the Plan will include written certification from a qualified professional engineer that the initial and any amendments to the IDF Plan meet the requirements of the CCR Rule.

A record of amendments to the Plan will be tracked below. The latest version of the IDF Plan will be noted on the front cover of the Plan.

Version	Date	Description of Changes Made
1	16 October 2016	Initial Issuance

§257.82(c)(3): Timeframes for preparing the initial plan

- i. Existing CCR surface impoundments. The owner or operator of the CCR unit must prepare the initial inflow design flood control system plan no later than October 17, 2016.*

This IDF control system plan has been prepared within the specified timeframe.

- ii. New CCR surface impoundments and any lateral expansion of a CCR surface impoundment. The owner or operator must prepare the initial inflow design flood control system plan no later than the date of initial receipt of CCR in the CCR unit.*

N/A – Pond 004 is an existing CCR impoundment.

§257.82(c)(4): Frequency for revising the plan. The owner or operator must prepare periodic inflow design flood control system plans required by paragraph (c)(1) of this section every five years. The date of completing the initial plan is the basis for establishing the deadline to complete the first periodic plan. The owner or operator may complete any required plan prior to the required deadline provided the owner or operator places the completed plan into the facility’s operating record within a reasonable amount of time. In all cases, the deadline for completing a subsequent plan is based on the date of completing the previous plan. For purposes of this paragraph (c)(4), the owner or operator has completed an inflow design flood control system plan when the plan has been placed in the facility’s operating record as required by § 257.105(g)(4).

This IDF Plan or any subsequent IDF Plan will be assessed and amended whenever there is a change in operation of the CCR impoundment that would substantially affect the IDF Plan or when unanticipated events necessitate a revision of the Plan either before or after closure activities have commenced.

§257.82(c)(5): The owner or operator must obtain a certification from a qualified professional engineer stating that the initial and periodic inflow design flood control system plans meet the requirements of this section.

I certify that the design of the flood control system referenced in this Inflow Design Flood Control System Plan for AECl's Pond 004 at the New Madrid Power Plant meets the USEPA's CCR Rule requirements of §257.82.

Signed: 


Consulting Engineer

Print Name: Steven F. Putrich
Missouri License No.: 2014035813
Title: Project Principal
Company: Haley & Aldrich, Inc.

Professional Engineer's Seal and date:



LUCAS, ANDY
G:\40616 AECI-COR ELG MANAGEMENT SUPPORT\CAD-NM\POND004\FIG-1 SITE PLAN.DWG
Printed: 9/19/2016 9:54 AM
Layout: SITE PLAN



LEGEND

- EXISTING MINOR CONTOUR
- 300- EXISTING MAJOR CONTOUR
- - - - APPROXIMATE IMPOUNDMENT BOUNDARY
- — — ROAD
- WATER

NOTES

1. EXISTING TOPOGRAPHY BASED ON LIDAR DATA RECEIVED FROM AECI CONDUCTED BY PICTOMETRY INTERNATIONAL CORP. AERIAL SURVEY CONDUCTED BETWEEN 4-8 OCTOBER 2014.




ASSOCIATED ELECTRIC COOPERATIVE, INC.
NEW MADRID POWER PLANT
NEW MADRID, MO

**POND 004
SITE PLAN**


SCALE: AS SHOWN
OCTOBER 2016

FIGURE 1



Appendix A



Pond 004 Subcatchment



Pond 004



AECI_New Madrid_Pond 004_Stormwater_Average Flow

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 08262 © 2013 HydroCAD Software Solutions LLC

Printed 10/14/2016

Page 2

Area Listing (all nodes)

Area (acres)	CN	Description (subcatchment-numbers)
6.541	84	50-75% Grass cover, Fair, HSG D (004S)
3.431	98	Water Surface, HSG A (004S)
9.972	89	TOTAL AREA

AECI_New Madrid_Pond 004_Stormwater_Average Flow

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 08262 © 2013 HydroCAD Software Solutions LLC

Printed 10/14/2016

Page 3

Soil Listing (all nodes)

Area (acres)	Soil Group	Subcatchment Numbers
3.431	HSG A	004S
0.000	HSG B	
0.000	HSG C	
6.541	HSG D	004S
0.000	Other	
9.972		TOTAL AREA

AECI_New Madrid_Pond 004_Stormwater_Average Flow

Prepared by {enter your company name here}

HydroCAD® 10.00 s/n 08262 © 2013 HydroCAD Software Solutions LLC

Printed 10/14/2016

Page 4

Ground Covers (all nodes)

HSG-A (acres)	HSG-B (acres)	HSG-C (acres)	HSG-D (acres)	Other (acres)	Total (acres)	Ground Cover	Subcatchment Numbers
0.000	0.000	0.000	6.541	0.000	6.541	50-75% Grass cover, Fair	004S
3.431	0.000	0.000	0.000	0.000	3.431	Water Surface	004S
3.431	0.000	0.000	6.541	0.000	9.972	TOTAL AREA	

AECI_New Madrid_Pond 004_Stormwater_Average Flow

Prepared by {enter your company name here}

Printed 10/14/2016

HydroCAD® 10.00 s/n 08262 © 2013 HydroCAD Software Solutions LLC

Page 5

Pipe Listing (all nodes)

Line#	Node Number	In-Invert (feet)	Out-Invert (feet)	Length (feet)	Slope (ft/ft)	n	Diam/Width (inches)	Height (inches)	Inside-Fill (inches)
1	P004	289.30	284.00	200.0	0.0265	0.025	18.0	0.0	0.0

AECI_New Madrid_Pond 004_Stormwater_Average *Type II 24-hr 1000-Yr Rainfall=11.60"*

Prepared by {enter your company name here}

Printed 10/14/2016

HydroCAD® 10.00 s/n 08262 © 2013 HydroCAD Software Solutions LLC

Page 6

Time span=0.00-144.00 hrs, dt=0.01 hrs, 14401 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment004S: Pond 004

Runoff Area=9.972 ac 34.41% Impervious Runoff Depth=10.24"
Flow Length=2,550' Tc=30.8 min CN=89 Runoff=81.83 cfs 8.508 af

Pond P004: Pond 004

Peak Elev=297.16' Storage=12.211 af Inflow=84.62 cfs 41.714 af
Outflow=12.66 cfs 39.764 af

Total Runoff Area = 9.972 ac Runoff Volume = 8.508 af Average Runoff Depth = 10.24"
65.59% Pervious = 6.541 ac 34.41% Impervious = 3.431 ac

Summary for Subcatchment 004S: Pond 004 Subcatchment

Runoff = 81.83 cfs @ 12.22 hrs, Volume= 8.508 af, Depth=10.24"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-144.00 hrs, dt= 0.01 hrs
 Type II 24-hr 1000-Yr Rainfall=11.60"

Area (ac)	CN	Description
3.431	98	Water Surface, HSG A
6.541	84	50-75% Grass cover, Fair, HSG D
9.972	89	Weighted Average
6.541		65.59% Pervious Area
3.431		34.41% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
14.5	100	0.0100	0.12		Sheet Flow, Grass: Short n= 0.150 P2= 2.56"
8.5	447	0.0157	0.88		Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps
7.8	2,003	0.0010	4.27	558.53	Channel Flow, Area= 130.8 sf Perim= 38.2' r= 3.42' n= 0.025 Earth, clean & winding
30.8	2,550	Total			

Subcatchment 004S: Pond 004 Subcatchment

Hydrograph



Summary for Pond P004: Pond 004

Inflow Area = 9.972 ac, 34.41% Impervious, Inflow Depth > 50.20" for 1000-Yr event
 Inflow = 84.62 cfs @ 12.22 hrs, Volume= 41.714 af, Incl. 2.79 cfs Base Flow
 Outflow = 12.66 cfs @ 13.22 hrs, Volume= 39.764 af, Atten= 85%, Lag= 59.9 min
 Primary = 12.66 cfs @ 13.22 hrs, Volume= 39.764 af

Routing by Stor-Ind method, Time Span= 0.00-144.00 hrs, dt= 0.01 hrs
 Starting Elev= 295.60' Surf.Area= 3.894 ac Storage= 5.847 af
 Peak Elev= 297.16' @ 13.22 hrs Surf.Area= 4.218 ac Storage= 12.211 af (6.365 af above start)

Plug-Flow detention time= 1,672.4 min calculated for 33.913 af (81% of inflow)
 Center-of-Mass det. time= 218.3 min (3,817.9 - 3,599.6)


Volume	Invert	Avail.Storage	Storage Description
#1	294.00'	30.306 af	Custom Stage Data (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (acres)	Inc.Store (acre-feet)	Cum.Store (acre-feet)
294.00	3.431	0.000	0.000
295.00	3.704	3.568	3.568
296.00	4.020	3.862	7.430
297.00	4.191	4.106	11.535
298.00	4.357	4.274	15.809
299.00	4.638	4.497	20.306
300.00	4.986	4.812	25.119
301.00	5.389	5.187	30.306


Device	Routing	Invert	Outlet Devices
#1	Primary	289.30'	18.0" Round Culvert L= 200.0' RCP, rounded edge headwall, Ke= 0.100 Inlet / Outlet Invert= 289.30' / 284.00' S= 0.0265 1/' Cc= 0.900 n= 0.025 Corrugated metal, Flow Area= 1.77 sf
#2	Device 1	295.60'	3.0' long x 1.2' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.66 2.69 2.71 2.78 2.89 2.99 3.09 3.20 3.21 3.19 3.30 3.32

Primary OutFlow Max=12.66 cfs @ 13.22 hrs HW=297.16' (Free Discharge)
 1=Culvert (Barrel Controls 12.66 cfs @ 7.17 fps)
 2=Broad-Crested Rectangular Weir (Passes 12.66 cfs of 18.59 cfs potential flow)



Pond P004: Pond 004

Hydrograph







Pond 004 Subcatchment



Plant Inflow

Pond 004



AECI_New Madrid_Pond 004_Stormwater_Maximum Flow 12-hr

Prepared by {enter your company name here}

Printed 10/14/2016

HydroCAD® 10.00 s/n 08262 © 2013 HydroCAD Software Solutions LLC

Page 2

Area Listing (all nodes)

Area (acres)	CN	Description (subcatchment-numbers)
6.541	84	50-75% Grass cover, Fair, HSG D (004S)
3.431	98	Water Surface, HSG A (004S)
9.972	89	TOTAL AREA

AECI_New Madrid_Pond 004_Stormwater_Maximum Flow 12-hr

Prepared by {enter your company name here}

Printed 10/14/2016

HydroCAD® 10.00 s/n 08262 © 2013 HydroCAD Software Solutions LLC

Page 3

Soil Listing (all nodes)

Area (acres)	Soil Group	Subcatchment Numbers
3.431	HSG A	004S
0.000	HSG B	
0.000	HSG C	
6.541	HSG D	004S
0.000	Other	
9.972		TOTAL AREA

AECI_New Madrid_Pond 004_Stormwater_Maximum Flow 12-hr

Prepared by {enter your company name here}

Printed 10/14/2016

HydroCAD® 10.00 s/n 08262 © 2013 HydroCAD Software Solutions LLC

Page 4

Ground Covers (all nodes)

HSG-A (acres)	HSG-B (acres)	HSG-C (acres)	HSG-D (acres)	Other (acres)	Total (acres)	Ground Cover	Subcatchment Numbers
0.000	0.000	0.000	6.541	0.000	6.541	50-75% Grass cover, Fair	004S
3.431	0.000	0.000	0.000	0.000	3.431	Water Surface	004S
3.431	0.000	0.000	6.541	0.000	9.972	TOTAL AREA	

AECI_New Madrid_Pond 004_Stormwater_Maximum Flow 12-hr

Prepared by {enter your company name here}

Printed 10/14/2016

HydroCAD® 10.00 s/n 08262 © 2013 HydroCAD Software Solutions LLC

Page 5

Pipe Listing (all nodes)

Line#	Node Number	In-Invert (feet)	Out-Invert (feet)	Length (feet)	Slope (ft/ft)	n	Diam/Width (inches)	Height (inches)	Inside-Fill (inches)
1	P004	289.30	284.00	200.0	0.0265	0.025	18.0	0.0	0.0

AECI_New Madrid_Pond 004_Stormwater_Maximum*Type II 24-hr 1000-Yr Rainfall=11.60"*

Prepared by {enter your company name here}

Printed 10/14/2016

HydroCAD® 10.00 s/n 08262 © 2013 HydroCAD Software Solutions LLC

Page 6

Time span=0.00-144.00 hrs, dt=0.01 hrs, 14401 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment 004S: Pond 004

Runoff Area=9.972 ac 34.41% Impervious Runoff Depth=10.24"
Flow Length=2,550' Tc=30.8 min CN=89 Runoff=81.83 cfs 8.508 af

Pond P004: Pond 004

Peak Elev=298.66' Storage=34.593 af Inflow=104.11 cfs 46.003 af
Outflow=13.45 cfs 45.986 af

Link PI: Plant Inflow

Manual Hydrograph Inflow=22.28 cfs 37.495 af
Primary=22.28 cfs 37.495 af

Total Runoff Area = 9.972 ac Runoff Volume = 8.508 af Average Runoff Depth = 10.24"
65.59% Pervious = 6.541 ac 34.41% Impervious = 3.431 ac

Summary for Subcatchment 004S: Pond 004 Subcatchment

Runoff = 81.83 cfs @ 12.22 hrs, Volume= 8.508 af, Depth=10.24"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-144.00 hrs, dt= 0.01 hrs
 Type II 24-hr 1000-Yr Rainfall=11.60"

Area (ac)	CN	Description
3.431	98	Water Surface, HSG A
6.541	84	50-75% Grass cover, Fair, HSG D
9.972	89	Weighted Average
6.541		65.59% Pervious Area
3.431		34.41% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
14.5	100	0.0100	0.12		Sheet Flow, Grass: Short n= 0.150 P2= 2.56"
8.5	447	0.0157	0.88		Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps
7.8	2,003	0.0010	4.27	558.53	Channel Flow, Area= 130.8 sf Perim= 38.2' r= 3.42' n= 0.025 Earth, clean & winding
30.8	2,550	Total			

Subcatchment 004S: Pond 004 Subcatchment

Hydrograph



Summary for Pond P004: Pond 004

Inflow Area = 9.972 ac, 34.41% Impervious, Inflow Depth = 55.36" for 1000-Yr event
 Inflow = 104.11 cfs @ 12.22 hrs, Volume= 46.003 af
 Outflow = 13.45 cfs @ 18.56 hrs, Volume= 45.986 af, Atten= 87%, Lag= 380.0 min
 Primary = 13.45 cfs @ 18.56 hrs, Volume= 45.986 af

Routing by Stor-Ind method, Time Span= 0.00-144.00 hrs, dt= 0.01 hrs
 Starting Elev= 293.60' Surf.Area= 3.387 ac Storage= 14.467 af
 Peak Elev= 298.66' @ 18.56 hrs Surf.Area= 4.543 ac Storage= 34.593 af (20.126 af above start)

Plug-Flow detention time= 1,696.9 min calculated for 31.518 af (69% of inflow)
 Center-of-Mass det. time= 634.4 min (1,884.8 - 1,250.4)


Volume	Invert	Avail.Storage	Storage Description
#1	289.00'	46.137 af	Custom Stage Data (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (acres)	Inc.Store (acre-feet)	Cum.Store (acre-feet)
289.00	2.910	0.000	0.000
290.00	3.010	2.960	2.960
291.00	3.110	3.060	6.020
292.00	3.220	3.165	9.185
293.00	3.320	3.270	12.455
294.00	3.431	3.376	15.831
295.00	3.704	3.568	19.398
296.00	4.020	3.862	23.260
297.00	4.191	4.106	27.366
298.00	4.357	4.274	31.640
299.00	4.638	4.497	36.137
300.00	4.986	4.812	40.949
301.00	5.389	5.187	46.137

Device	Routing	Invert	Outlet Devices
#1	Primary	289.30'	18.0" Round Culvert L= 200.0' RCP, rounded edge headwall, Ke= 0.100 Inlet / Outlet Invert= 289.30' / 284.00' S= 0.0265 1/1' Cc= 0.900 n= 0.025 Corrugated metal, Flow Area= 1.77 sf
#2	Device 1	293.60'	3.0' long x 1.2' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.66 2.69 2.71 2.78 2.89 2.99 3.09 3.20 3.21 3.19 3.30 3.32

Primary OutFlow Max=13.45 cfs @ 18.56 hrs HW=298.66' (Free Discharge)
 ↑ **1=Culvert** (Barrel Controls 13.45 cfs @ 7.61 fps)
 ↑ **2=Broad-Crested Rectangular Weir** (Passes 13.45 cfs of 113.49 cfs potential flow)

Pond P004: Pond 004

Hydrograph



Summary for Link PI: Plant Inflow


Inflow = 22.28 cfs @ 6.00 hrs, Volume= 37.495 af
 Primary = 22.28 cfs @ 6.00 hrs, Volume= 37.495 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-144.00 hrs, dt= 0.01 hrs

73 Point manual hydrograph, To= 0.00 hrs, dt= 1.00 hrs, cfs =

2.78	2.78	2.78	2.78	2.78	2.78	22.28	22.28	22.28	22.28
22.28	22.28	22.28	22.28	22.28	22.28	22.28	22.28	22.28	2.78
2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78
2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78
2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78
2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78
2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78
2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78
2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78
2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78	2.78

Link PI: Plant Inflow
Hydrograph



Appendix B


TYPE OF OUTLET (Mark all that apply)

 Open Channel Spillway


- Trapezoidal
- Triangular
- Rectangular
- Irregular

- depth
- bottom (or average) width
- top width


TRAPEZOIDAL




TRIANGULAR



RECTANGULAR



IRREGULAR




 x **Outlet**

 18" inside diameter

Material

- x corrugated metal
- welded steel
- concrete
- plastic (hdpe, pvc, etc.)
- other (specify) _____



Is water flowing through the outlet? YES x NO _____

 No Outlet

 Other Type of Outlet (specify) _____

The Impoundment was Designed By Burns & McDonnell

Appendix C

NOAA's National Weather Service
Hydrometeorological Design Studies Center
 Precipitation Frequency Data Server (PFDS)



Home Site Map News Organization

Search NWS All NOAA

General Info

- Homepage
- Current Projects
- FAQ
- Glossary

Precipitation Frequency (PF)

- PF Data Server
- PF in GIS Format
- PF Maps
- Temporal Distr.
- Time Series Data
- PFDS Perform.
- PF Documents

Probable Maximum Precipitation (PMP)

- PMP Documents

Miscellaneous

- Publications
- AEP Storm Analysis
- Record Precipitation

Contact Us

- Inquiries
- List-server



NOAA ATLAS 14 POINT PRECIPITATION FREQUENCY ESTIMATES: TN

Data description

Data type: Units: Time series type:

Select location

1) Manually:

a) By location

Decimal degrees Degrees, decimal minutes Degrees, minutes, seconds

Latitude: N Longitude: E

b) By station

[Click here for a list of stations used in frequency analysis for TN:](#)

Select station

c) By address

Search

2) Use map:

a) Select location

Move crosshair or double click

b) Click on station icon

Show stations on map

Location information:

Name: Tiptonville, Tennessee, US

Latitude: 36.5072° N

Longitude: -89.5571° E

Elevation: 305.11 ft**

* Source: ESRI Maps
** Source: USGS

POINT PRECIPITATION FREQUENCY (PF) ESTIMATES
 WITH 90% CONFIDENCE INTERVALS AND SUPPLEMENTARY INFORMATION
 NOAA Atlas 14, Volume 8, Version 2

PF tabular PF graphical Supplementary information [Print page](#)

PDS-based precipitation frequency estimates with 90% confidence intervals (in inches) ¹										
Duration	Average recurrence interval (years)									
	1	2	5	10	25	50	100	200	500	1000
5-min	0.411 (0.330-0.515)	0.476 (0.382-0.596)	0.581 (0.465-0.730)	0.669 (0.533-0.843)	0.792 (0.611-1.02)	0.886 (0.670-1.15)	0.982 (0.719-1.30)	1.08 (0.761-1.45)	1.21 (0.823-1.66)	1.31 (0.870-1.82)
10-min	0.602 (0.484-0.754)	0.696 (0.559-0.873)	0.851 (0.681-1.07)	0.980 (0.780-1.23)	1.16 (0.894-1.49)	1.30 (0.981-1.69)	1.44 (1.05-1.90)	1.58 (1.11-2.13)	1.77 (1.21-2.43)	1.92 (1.27-2.66)
15-min	0.735 (0.590-0.920)	0.849 (0.681-1.06)	1.04 (0.830-1.30)	1.20 (0.951-1.50)	1.41 (1.09-1.82)	1.58 (1.20-2.06)	1.75 (1.28-2.32)	1.93 (1.36-2.59)	2.16 (1.47-2.96)	2.33 (1.55-3.24)

PFDS: Contiguous US

30-min	1.05 (0.846-1.32)	1.22 (0.981-1.53)	1.50 (1.20-1.88)	1.73 (1.38-2.18)	2.05 (1.58-2.63)	2.29 (1.73-2.98)	2.54 (1.86-3.35)	2.79 (1.97-3.75)	3.12 (2.13-4.28)	3.37 (2.25-4.68)
60-min	1.39 (1.12-1.74)	1.61 (1.29-2.01)	1.96 (1.57-2.46)	2.27 (1.80-2.85)	2.69 (2.08-3.48)	3.03 (2.29-3.95)	3.38 (2.48-4.47)	3.73 (2.64-5.04)	4.22 (2.88-5.80)	4.59 (3.05-6.38)
2-hr	1.73 (1.41-2.14)	1.99 (1.61-2.46)	2.43 (1.97-3.01)	2.81 (2.26-3.49)	3.34 (2.62-4.27)	3.77 (2.89-4.86)	4.22 (3.13-5.52)	4.68 (3.35-6.25)	5.31 (3.67-7.23)	5.81 (3.91-7.98)
3-hr	1.96 (1.60-2.40)	2.24 (1.83-2.75)	2.73 (2.22-3.35)	3.15 (2.56-3.89)	3.77 (2.98-4.78)	4.26 (3.29-5.46)	4.78 (3.58-6.24)	5.33 (3.85-7.09)	6.09 (4.24-8.26)	6.69 (4.54-9.14)
6-hr	2.39 (1.98-2.90)	2.72 (2.25-3.30)	3.31 (2.73-4.02)	3.82 (3.14-4.66)	4.58 (3.67-5.75)	5.20 (4.07-6.59)	5.85 (4.44-7.54)	6.54 (4.78-8.61)	7.51 (5.29-10.1)	8.29 (5.68-11.2)
12-hr	2.88 (2.42-3.44)	3.29 (2.76-3.94)	4.00 (3.34-4.80)	4.62 (3.84-5.56)	5.53 (4.48-6.86)	6.27 (4.97-7.84)	7.05 (5.41-8.97)	7.87 (5.81-10.2)	9.01 (6.42-11.9)	9.92 (6.88-13.3)
24-hr	3.41 (2.90-4.03)	3.93 (3.33-4.64)	4.80 (4.06-5.68)	5.55 (4.67-6.59)	6.63 (5.42-8.09)	7.49 (5.99-9.23)	8.37 (6.50-10.5)	9.30 (6.94-11.9)	10.6 (7.61-13.8)	11.6 (8.12-15.3)
2-day	3.98 (3.43-4.64)	4.62 (3.97-5.39)	5.68 (4.87-6.64)	6.58 (5.60-7.70)	7.83 (6.47-9.40)	8.81 (7.13-10.7)	9.80 (7.68-12.1)	10.8 (8.17-13.7)	12.2 (8.88-15.7)	13.3 (9.42-17.3)
3-day	4.38 (3.79-5.05)	5.07 (4.38-5.86)	6.21 (5.36-7.20)	7.18 (6.16-8.34)	8.53 (7.10-10.2)	9.59 (7.81-11.6)	10.7 (8.42-13.1)	11.8 (8.94-14.8)	13.3 (9.72-17.0)	14.4 (10.3-18.7)
4-day	4.68 (4.08-5.38)	5.41 (4.71-6.21)	6.61 (5.74-7.62)	7.63 (6.59-8.82)	9.07 (7.59-10.8)	10.2 (8.36-12.2)	11.3 (9.01-13.9)	12.5 (9.58-15.7)	14.1 (10.4-18.1)	15.4 (11.1-19.9)
7-day	5.41 (4.76-6.14)	6.21 (5.46-7.06)	7.55 (6.62-8.61)	8.71 (7.59-9.95)	10.3 (8.77-12.2)	11.6 (9.65-13.8)	13.0 (10.4-15.7)	14.4 (11.1-17.8)	16.3 (12.1-20.6)	17.8 (12.9-22.7)
10-day	6.08 (5.39-6.86)	6.93 (6.14-7.83)	8.37 (7.39-9.47)	9.61 (8.43-10.9)	11.4 (9.70-13.3)	12.8 (10.7-15.1)	14.2 (11.5-17.1)	15.7 (12.2-19.3)	17.8 (13.3-22.3)	19.4 (14.2-24.6)
20-day	8.19 (7.35-9.10)	9.17 (8.23-10.2)	10.8 (9.66-12.0)	12.2 (10.8-13.6)	14.1 (12.2-16.2)	15.6 (13.2-18.1)	17.1 (14.0-20.3)	18.7 (14.7-22.7)	20.8 (15.8-25.8)	22.4 (16.6-28.2)
30-day	10.0 (9.05-11.0)	11.1 (10.1-12.3)	13.0 (11.7-14.3)	14.5 (13.0-16.1)	16.5 (14.3-18.7)	18.1 (15.4-20.8)	19.6 (16.2-23.0)	21.2 (16.8-25.5)	23.2 (17.8-28.6)	24.8 (18.5-31.0)
45-day	12.3 (11.2-13.5)	13.7 (12.5-15.0)	15.8 (14.4-17.4)	17.6 (15.9-19.3)	19.8 (17.3-22.3)	21.5 (18.4-24.5)	23.1 (19.2-26.9)	24.7 (19.7-29.4)	26.7 (20.5-32.5)	28.1 (21.1-34.9)
60-day	14.3 (13.1-15.5)	15.9 (14.6-17.3)	18.4 (16.8-20.0)	20.3 (18.5-22.3)	22.9 (20.0-25.4)	24.7 (21.2-27.9)	26.4 (22.0-30.4)	28.0 (22.4-33.1)	30.0 (23.1-36.2)	31.3 (23.7-38.7)

¹ Precipitation frequency (PF) estimates in this table are based on frequency analysis of partial duration series (PDS).

Numbers in parenthesis are PF estimates at lower and upper bounds of the 90% confidence interval. The probability that precipitation frequency estimates (for a given duration and average recurrence interval) will be greater than the upper bound (or less than the lower bound) is 5%. Estimates at upper bounds are not checked against probable maximum precipitation (PMP) estimates and may be higher than currently valid PMP values.

Please refer to NOAA Atlas 14 document for more information.

Estimates from the table in CSV format:

Main Link Categories:

[Home](#) | [OWP\(OHD\)](#)

US Department of Commerce
National Oceanic and Atmospheric Administration
National Weather Service
Office of Water Prediction (OWP)
1325 East West Highway
Silver Spring, MD 20910
Page Author: [HDSC webmaster](#)
Page last modified: August 27, 2014

Map Disclaimer
Disclaimer
Credits
Glossary

Privacy P
About
Career Opportu